

LI-PS 850–2.200VA

Betrouwbare noodstroomoplossingen voor elke situatie



The UPS Factory

The UPS Factory is gespecialiseerd in hoogwaardige noodstroomoplossingen en leveren betrouwbare UPS-systemen die continuïteit en veiligheid garanderen voor professionele toepassingen.

LI-PS

- ✓ Ingebouwde spanningsregelaar voor stabiele stroomkwaliteit en noodstroom
- ✓ Meer dan 4 uur autonomietijd met een modem als belasting.
- ✓ Meest praktische en compacte oplossing
- ✓ Supersnelle lader (2–4 uur naar 90%)
- ✓ USB HID-interface voor monitoring en automatische shutdown (Windows, Mac, Linux compatibel)

Typische Toepassingen

-  PC's en werkstations
-  Netwerk- en telecomapparatuur
-  CCTV, Alarm Systemen, Roldeur- en luiken, brandschermen



Voorzijde
850VA



Achterzijde
850VA



Voorzijde
1200/2200 VA



Achterzijde
1200/2200 VA

LI-PS 850–2.200VA

Betrouwbare noodstroomoplossingen voor elke situatie



MODEL		LI-PS-850	LI-PS-1200	LI-PS-2200
CAPACITY		850VA/480W	1200VA/600W	2200VA/1200W
INPUT	Input Voltage Range	220V: 162-268VAC / 230V: 170-280VAC / 240V: 177-290VAC		
	Frequency Range	45-55Hz/5 5-65Hz		
	Input connection	IEC-C14/10A or fixed power cord with Schuko plug 1.2m		
OUTPUT	Output Power Factor	0.56	0.5	0.55
	Nominal Output Voltage	220/230/240 V _{AC}		
	Voltage Regulation (Line Mode)	±15%		
	Voltage Regulation (Battery Mode)	±10%		
	Frequency Range (Battery Mode)	50/60Hz ± 1Hz		
	Output Waveform	Modified sine wave		
	Output socket	(2) Schuko	(4) Schuko	
EFFICIENCY	Line Mode	95%		
	AVR Mode	88%		
	Battery Mode	60%		
BATTERY	Battery Type	12V/9Ah	12V/7Ah	12V/9Ah
	Number of Internal Battery	1	2	2
	Rated Battery Voltage	12V _{DC}	24V _{DC}	24V _{DC}
	Backup Time (@ Typical PC load)	20 min	40 min	50 min
	Recharge Time (to 90%)	2-4 hours		
TRANSFER TIME	Battery Mode ↔ Line Mode	3-8 ms typical		
DISPLAY		LCD		
AUDIBLE ALARM		YES		
DIMENSION	WxHxD	100 x 143 x 300 mm	139 X 195 x 364 mm	
NET WEIGHT		4.9kg	7.9kg	9.1kg
ENVIRONMENT	Operating Temperature	0-40° C		
	Noise Level	<40dB		<45dB
INTERFACE	USB	Yes		
	External Slot	No		
	TVSS protection	Option RJ45		

The UPS Factory bv
Website: www.TheUPSFactory.nl
E-mail: info@TheUPSFactory.nl
Tel: +31 (0)186 684 088

